



Food
Service
Solutions

EQUIPMENT CATALOG

Catalog No. 114 NVCAT
Published January 1, 2024
Pricing published separately



800.338.9886 | sales@nu-vu.com | www.nu-vu.com

Welcome to our January 1, 2024 product catalog!

NU-VU® has evolved from being the leader in on-premise sub shop baking into many other food service segments. Our product line reflects an expansion into new markets including schools, restaurants, C-stores and more. NU-VU® is the highest quality product for your foodservice needs.

As you go through the catalog, always remember that the products are designed with the operator in mind. Easy-to-use and intuitive controls, best in class performance, the highest quality material, and superior airflow are among the many features that make NU-VU® one of the proudest brands within the Middleby division.



We know baking, proofing, holding, cooking, smoking, and much more!

- **Convenience Stores**
- **Delis**
- **Cafes**
- **Schools**
- **Health Care Facilities**
- **Independent Living**
- **Restaurants**
- **Chains**
- **Sub Shops**

Table of Contents

 Convection Ovens	4-8
 Oven/Proofer Combinations	9-12
 Proofers	13
 Smokers	14
 Bread Cabinets & Racks	15-16
 Terms of Sale	17
 Warranty	17
 Terminology	18-19
 Index	20



CHOOSE YOUR

NU-VU OVEN



NU-VU® Convection Ovens

Features

	NU-VU® OVENS					
	XO-1	XO-1M	RM-5T	NC03	NC05	NC0T5
V-Air Even Air Flow			X			
Jet Air Reversing Fan						
Offered in Electric	X	X	X	X	X	X
Offered in Gas						
Half Size Sheet Pan Capacity	3	5	10	3	5	5
Full Size Sheet Pan Capacity			5			
Cook N' Hold			optional			
Manual Controls	X	X	X	X	X	
Programmable Controls						X
Multispeed Fan	X	X	optional			X
Internal Steam 'IGS'	optional	optional	optional			
Fan Delay						
Moisture Evacuation System						

Production Capacity

	NU-VU® BAKING OVENS AND OVEN-PROOFERS (per hour)								
	State	Bake Time (Min)	Bake Temp (F)	NC03/XO-1 (half-pan)	NC05/XO-1M (half pan)	NC0T5 (half pan) (two speed fan)	QB3/9	QB4/8	RM5-T/QBT5 -10
Bagels (16 per pan)	Fresh	15	375	96	X	160	X	X	320
Dinner rolls (16 per pan)	Fresh	15-18	350	96	160	160	192	256	320
Sub rolls 12" (10 per pan)	Fresh	15-18	350	X	X	100	120	160	200
French Baguette (5 per pan)	Fresh	20-25	350	X	X	X	X	X	X
Croissants (15 per pan)	Frozen	12-15	350	90	188	188	180	240	375
Croissants (15 per pan)	Fresh	12-15	350	X	X	188	X	X	X
8" Pies (6 per shelf)	Fresh	30-35	375	4 (2 per shelf)	12 (2 per shelf)	12 (2 per shelf)	X	X	X
Muffins (15 per pan)	Fresh	18-22	350	68	113	113	135	180	225
Muffins (24 per pan)	Fresh	18-22	350	108	180	180	216	288	360
Cakes 8" (6 per shelf)	Fresh	18-22	350	X	X	12 (2 per shelf)	54	72	90
Quiches 8" (6 per shelf)	Fresh	30-35	350	X	12 (2 per)	12 (2 per shelf)	X	X	X
Cookies (18 per pan)	Frozen	8-10	300	162	270	270	324	432	540
Danish (15 per pan)	Fresh	12-15	350	90	188	188	180	240	375
Biscuits (15 per pan)	Fresh	8-10	350	135	225	225	270	360	450
Bread (4 strapped pan)	Fresh	30-35	350	X	X	X	X	X	32
Cinnamon rolls (8/half pan)	Fresh	15-18	325	96	160	160	192	256	320

NU-VU® Countertop Convection Ovens RM-5T

Features

- Temperature up to 425°F (218°C)
- V-Air air circulation for even baking
- 1 standard speed fan
- Steam vent
- Indicator light for thermostat
- Slam cam handle

Construction

- Stainless steel finish
- Fully insulated
- 6" adjustable legs
- Left or right hinged, field-reversible door
- Cool to the touch dual pane, full view window; tool-less cleaning
- 2 year parts, 1 year labor warranty

Options

- Two-speed fan (RMFAN)
- Internal steam (RMIS)
- Water filter, recommended if using internal steam option (112-9166)
- Solid door
- Cart on swivel casters with or without pan slides
- Stand with or without pan slides
- Stacking kit (RMSTACK)
- Pass-thru option (RMPT)
- Cook & Hold option (RMCNA)
- Wire shelf racks, each (4FM7023P)

**Great for par-baked
and frozen pastries!**



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Interior Dimensions in (mm)			Pan Capacity	Shelf Spacing in (mm)	Water Inlet In (mm)	Electrical System *Ground wire not included.					
		W	D	H	W	D	H				Volts	Phases	Amps	kW	Wires*	Hz
RM-5T	425 (192)	30" (762)	37 7/8" (962)	41 3/4" (1060)	18 3/4" (476)	29 3/4" (756)	22" (559)	5 (full pans)	4" (102)	1/4" (6)	208 240	1/3 1/3	37/30 32/26	7 7	2/3 2/3	60 60

Faster Bake Time



RM-5T
shown with pass-thru option



RM-5T

NU-VU® Countertop Convection Ovens NCO Series

NCO3/NCO5

- Stainless steel finish
- Press-fit gasket for easy cleaning
- Temperature up to 550°F (288°C)
- Manual controls
- Indicator light for thermostat
- Door switch cutoff for fan blower
- 4" adjustable legs (102mm)
- Press-fit removable door gasket for easy cleaning
- Dual pane, cool-to-touch door
- Lift up removable side racks
- 60 minute timer; adjustable buzzer volume
- Left hinged door
- Two year parts and one year labor warranty

NCOT5

- Stainless steel finish
- Press-fit gasket for easy cleaning
- Programmable touchscreen control with icons
 - 18 programs
 - 3 stage baking
- Temperature up to 550°F (288°C)
- Two speed fan
- Door switch cutoff for fan blower
- 4" adjustable legs (102mm)
- Press -fit removable door gasket for easy cleaning
- Dual pane, cool-to-touch door
- Lift up removable side racks
- Left hinged door
- ENERGY STAR
- Two year parts and one year labor warranty

Options

- Wire shelf (NCOWS)
- Cart with pan slides (98-9450)
- Ventless (NCOT5 only) (suffix -V)



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Interior Dimensions in (mm)			Pan Capacity (13"x18")	Shelf Spacing in (mm)	Electrical System *Ground wire not included.						
		W	D	H	W	D	H			Volts	Phases	Amps	kW	Wires*	Hz	NEMA
NCO3	165 (74)	29 1/8" (740)	27 7/8" (708)	21 1/2" (546)	18 3/8" (467)	14 3/8" (365)	11 3/4" (298)	3	3 1/2" (89)	120	1	16	1.7	2	60	5-20P
NCO5	205 (92)	29 1/8" (740)	27 7/8" (708)	26 7/8" (683)	18 3/8" (467)	14 3/8" (365)	16 7/8" (429)	5	3 1/8" (79)	208 240	1 1	21 18	4 4	2 2	60 60	- -
NCOT5	205 (92)	29 1/8" (740)	27 7/8" (708)	26 7/8" (683)	18 3/8" (467)	14 3/8" (365)	16 7/8" (429)	5	3 1/8" (79)	208 240	1 1	21 18	4 4	2 2	60 60	6-30P 6-30P

Best in Class for Energy Efficiency



NCO3

**Incredibly even bake
with less waste!**



NCO5



NCOT5



NU-VU® Countertop Convection Ovens XO Series

Features

- Two speed fan
- Temperature up to 550°F (288°C)
- Indicator light for thermostat
- Manual controls
- Door switch cut-off for fan blower
- Adjustable buzzer

Construction

- Stainless steel finish; fully insulated
- Tempered glass door
- 4" adjustable legs
- Left hinged door
- 2 year parts, 1 year labor warranty

Options

- Internal steam (XOIS)
- Water filter, recommended if using internal steam option (112-9166)
- Solid door (XOSD)
- Stand on swivel casters with pan slides (98-9890-PS)
- Stand on swivel casters w/o pan slides (98-9800-NP)
- Stand with pan slides (98-9970-PS)
- Stand without pan slides (98-9970-NP)
- Catering conversion (XO-1 only): handles on each side and cord retainer (XOCC)
- Wire shelf racks (98-0125-B)
- Stacking kit (XOSTACK)



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Interior Dimensions in (mm)			Pan Capacity	Shelf Spacing in (mm)	Water Inlet ¹ in (mm)	Electrical System *Ground wire not included.						
		W	D	H	W	D	H				Volts	Phases	Amps	kW	Wires*	Hz	NEMA
XO-1	165 (74)	27 1/8" (689)	27 3/4" (705)	20" (508)	15 3/4" (400)	21 1/2" (546)	11 3/4" (298)	3 (half pans) 4 (half pans)	3 3/4" (95) 2" (51)	1/4" (6)	120	1	16.5	1.7	2	60	5-20P
XO-1M	205 (92)	27 1/8" (689)	27 3/4" (705)	25 1/8" (638)	15 3/4" (400)	21 1/2" (546)	16 3/4" (424)	4 (half pans) 5 (half pans)	3 5/8" (92) 2 7/8" (73)	1/4" (6)	208 240	1 1	21 19	4 4	2 2	60 60	- -

¹Water inlet: Only for internal steam option

Standard Two Speed Fan



XO-1



XO-1M

**Versatile space saver...
bakes and roasts!**



CHOOSE YOUR
OVEN/PROOFER



NU-VU® Oven/Proofer Combinations QB/QBT Series

	NU-VU® OVEN PROOFERS—FEATURES					
	QB-3/9	QBT-3/9	QB-4/8	QBT-4/8	QB-5/10	QBT-5/10
V-Air Even Air Flow	X	X	X	X	X	x
Jet Air Reversing Fan						
Half Size Sheet Pan Capacity	6/18	6/18	8/16	8/16	10/20	10/20
Full Size Sheet Pan Capacity	3/9	3/9	4/8	4/8	5/10	5/10
Cook N' Hold		X		X		X
Manual Controls	X		X		X	
Programmable Controls		X		X		X
Manual Fill Proofer	X		X	X	X	X
Automist Proofer	optional	X				
Autofill System			X	X	X	X
Multispeed Fan	optional			X		X
Internal Steam 'IGS'	optional					

Note: The QB series ovens are engineered, designed and built to be used in specific foodservice applications. They are intended for on-premise batch baking of a single dough product with specific profiles and baking parameters. They are not recommended for general market use, unless confirmed by NU-VU culinary support.



QBT-3/9



QB-3/9

NU-VU® Oven/Proofer Combinations QB/QBT Series

Features

- V-Air® technology
- Temperature up to 425°F (218°C)
- Dual Pane, cool-to-touch door
- QB Series
 - Manual fill proofer
 - Separate times for oven and proofer
 - Indicator light for thermostat
- QBT Series
 - Intuitive touch screen
 - Innovative proofer design with AutoMist technology
 - Automist proofing

Construction

- Stainless steel
- Magnetic door latches heavy duty casters
- Overflow drain and pan
- Left or right hinged
- Removable drip trough
- 2 year parts, 1 year labor warranty

Options

- QB Series
 - Internal steam for oven: QB-3/9 only (QBIS)
 - AutoMist® humidity (QBAM)
 - Warmer in proofer (QBW)
 - Two speed fan (QBFAN)
 - Wire shelf (112-0059-B)
 - Water filter, recommended (112-9166)
- QBT Series
 - Water filter, recommended(112-9166)
 - Wire shelf (GR17T26)
 - Warmer in proofer (QBW)



Specifications

Model	Crated Weight lbs (mm)	Overall Dimensions in (mm)			Interior Dimensions In (mm)						Pan Capacity (18"x26")		Shelf Spacing in (mm)		Water Inlet* In (mm)	Electrical System *Ground wire not included.					
		W	D	H	W	D	H	W	D	H	Oven	Proofer	Oven	Proofer		Volts	Phases	Amps	kW	Wires*	Hz
QB-3/9	590 (268)	36 1/8" (918)	28 5/8" (727)	77 3/4" (1975)	26 1/4" (667)	20 1/4" (514)	15" (381)	26 1/4" (667)	20 1/4" (514)	33 1/2" (851)	3	9	4" (102)	3 1/2" (89)	1/4" (6)	208 240	1/3 1/3	32/21 28/18	5.135 5.135	2/3 2/3	60 60
QBT-3/9	630 (286)	38 1/2" (978)	28 5/8" (727)	77 3/4" (1975)	26" (660)	18 1/2" (470)	14 1/2" (368)	26" (660)	18 1/2" (470)	33 3/8" (848)	3	9	4" (102)	3 1/2" (89)	1/4" (6)	208 240	1/3 1/3	32/21 28/18	5.2 5.2	3/4 3/4	60 60

*Water inlet: Only for AutoMist option.

Cost-Effective Batch Baking



**The gold standard
used by sub chains
worldwide!**

NU-VU® Oven/Proofer Combinations QB/QBT Series

Features

- V-Air® technology
- Temperature up to 425°F (220°C)
- Dual pane, cool-to-touch door
- Humidity system is both manual fill and/or autofill (1/4" water line required for autofill)
- Removable drip trough
- Overflow drain and pan
- Field reversible doors
- 2 year parts, 1 year labor warranty
- QB Series
 - Manual controls
 - Thermostat indicator light
- QBT Series
 - Intuitive touchscreen programmable controls
 - Innovative proofer design with Automist

Construction

- Stainless steel
- Heavy duty casters
- 2 year parts, 1 year labor warranty
- Fully insulated
- Magnetic door latches
- Overflow drain and pan
- Left or right hinged

Options

- QB Series
 - Warmer in proofer (QBW)
 - Two speed fan (QBFAN)
 - Wire shelf (112-0059-B)
 - Water filter, recommended (112-9166)
- QBT Series
 - Water filter, recommended(112-9166)
 - Wire shelf (GR17T26)
 - Warmer in proofer

**The gold
standard used
by sub chains
worldwide!**



Specifications

Model	Crated Weight In (mm)	Overall Dimensions in (mm)			Interior Dimensions in (mm)						Pan Capacity (18"x26")		Shelf Spacing		Water Inlet ¹ in (mm)	Electrical System *Ground wire not included.					
		W	D	H	W	D	H	W	D	H	Oven	Proofer	Oven	Proofer		Volts	Phases	Amps	kW	Wires*	Hz
QB-4/8	650 (295)	32 1/4" (820)	36 15/16" (939)	77 3/4" (1975)	18 1/4" (464)	28 1/2" (724)	18 1/4" (464)	18 3/8" (467)	28 5/8" (728)	30 1/4" (769)	4	8	4" (102)	3 1/2" (89)	1/4" (6)	208 240	1/3 1/3	39/27 36/24	7.9 7.9	2/3	60
QBT-4/8	650 (295)	32 1/4" (820)	36 15/16" (939)	77 3/4" (1975)	18 1/4" (464)	28 1/2" (724)	18 1/4" (464)	18 3/8" (467)	28 5/8" (728)	30 1/4" (769)	4	8	4" (102)	3 1/2" (89)	1/4" (6)	208 240	1/3 1/3	39/27 36/24	7.9 7.9	2/3	60
QB-5/10	750 (340)	32 1/4" (820)	36 15/16" (939)	83 7/8" (2131)	18 1/4" (464)	28 1/2" (724)	22 1/4" (566)	18 3/8" (467)	28 5/8" (728)	33 5/8" (855)	5	10	4" (102)	3 1/4" (83)	1/4" (6)	208 240	1/3 1/3	45/32 40/28	8.9 8.9	2/3	60
QBT-5/10	750 (340)	32 1/4" (820)	36 15/16" (939)	83 7/8" (2131)	18 1/4" (464)	28 1/2" (724)	22 1/4" (566)	18 3/8" (467)	28 5/8" (728)	33 5/8" (855)	5	10	4" (102)	3 1/4" (83)	1/4" (6)	208 240	1/3 1/3	45/32 40/28	8.9 8.9	2/3	60

¹Water inlet: Only for AutoFill water pan in proofer.

Highly Cost Effective



Note: The QB series ovens are engineered, designed and built to be used in specific foodservice applications. They are intended for on-premise batch baking of a single dough product with specific profiles and baking parameters. They are not recommended for general market use, unless confirmed by NU-VU culinary support.



QB-5/10

QBT-4/8

QBT-5/10

NU-VU® Proofers PRO/PROW Series

Features

- Electromechanical controls
- Indicator light for thermostat
- Temperature up to 110°F (45°C)
- Separate heat and humidity controls
- PRO Series
 - Fully insulated
 - Manual fill water pan
 - Cord and plug
- PROW Series
 - Fully insulated
 - Silicone rubber gasket on doors
 - AutoMist humidity system

Construction

- Stainless steel exterior; aluminum interior
- Heavy duty casters (PRO-16 and PROW-18)
- Left or right hinged
- 2 year parts, 1 year labor warranty

Options

- Warmer (PROWW)
- Set of 6" legs (PROWLEGS)
- Water filter for PROW Series, recommended (112-9166)



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Interior Dimensions in (mm)			Pan Capacity (18" x 26")	Shelf Spacing in (mm)	Water Inlet in (mm)	Electrical System *Ground wire not included.						
		W	D	H	W	D	H				Volts	Phases	Amps	kW	Wires*	Hz	NEMA
PRO-16	375 (170)	24 3/8" (619)	33 3/4" (857)	74 1/8" (1883)	18 3/8" (467)	28 7/8" (733)	57 3/8" (1457)	16	3 3/8" (86)	-	120	1	16	1.8	2	60	5-20P
PROW-18	525 (238)	25 1/8" (638)	34 5/8" (880)	78 3/8" (1991)	18 1/2" (470)	29" (737)	60" (1524)	18	3" (76)	1/4" (6)	208 240	1/3 1/3	12/10 11/9	2 2	2/3 2/3	60 60	- -

Ensures Consistent Results



PROW-18

Features

- Manual controls
- Cook temperature up to 350°F (177°C)
- Hold temperature up to 250°F (122°C)
- 24 hour timer
- Separate controls for smoke, heat, humidity, and cook and hold
- Bottom drip-safe pan for ease of cleaning
- Adjustable buzzer
- Meat Capacity:
 SMOKE6: 150 LBS
 SMOKE13: 350 LBS

Construction

- Stainless steel
- Internal smoke box
- 6" legs (SMOKE6)
- Casters (SMOKE13)
- 6 chrome racks (SMOKE6)
- 13 chrome racks (SMOKE13)
- Two year parts and one year labor warranty
- Left or right hinged (please specify)

Options

- Additional wire racks (101-0025-C)
- Casters in lieu of legs, SMOKE6
- Legs in lieu of casters, SMOKE13
- External smoke box
- Water filter, recommended (112-9166)
- Cart on swivel casters with pan slides, SMOKE6 (101-9006-PS)
- Cart on swivel casters without pan slides, SMOKE6 (101-9006-NP)
- Stand with pan slides, SMOKE6 (101-6100-PS)
- Stand without pan slides, SMOKE6 (101-6100-NP)



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Interior Dimensions in (mm)			Pan Capacity (18" x 26")	Shelf Spacing in (mm)	Water Inlet In (mm)	Electrical System *Ground wire not included.					
		W	D	H	W	D	H				Volts	Phases	Amps	kW	Wires*	Hz
SMOKE6	460 (208)	27 3/8" (696)	36 1/4" (921)	48 7/8" (1241)	18 3/4" (476)	29" (737)	26" (660)	6	3 1/2" (89)	1/4" (6)	208	1/3	13.5/10	2.5	2/3	60
											240	1/3	12/8.5	2.5	2/3	60
SMOKE13	750 (340)	27 3/8" (696)	36 1/4" (921)	78" (1981)	18 3/4" (476)	29" (737)	60" (1524)	13	3 1/2" (89)	1/4" (6)	208	1/3	23/19.5	4.5	2/3	60
											240	1/3	20.5/17	4.5	2/3	60

Exceptional Yield



Optional external smoker box



Smoke up to 350 lbs of meat!

NU-VU® Bread Cabinets HW / CR / HCR Series

HW

- Casters
- Fully enclosed cabinet
- Adjustable top vent
- Aluminum construction
- Polycarbonate door(s)
- Rubber gasket on doors
- Left or right hinged
- One year parts warranty

HCR18

- Casters
- Fully enclosed cabinet
- Aluminum construction
- Removable interior side walls
- Polycarbonate doors
- Magnetic door gaskets
- Left or right hinged
- One year parts warranty

CR18

- Casters
- Open rails on top for six (6) 18"x26" sheet pans
- Enclosed section for twelve (12) 18"x26" sheet pans
- Removable interior side walls
- Polycarbonate door
- Magnetic door gasket
- Lift off doors
- Left or right hinged
- One year parts warranty



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Pan Capacity (18" x 26")	Shelf Spacing in (mm)
		W	D	H		
HW-2-1/2G	75 (34)	22 1/8" (562)	29 3/8" (746)	39 1/2" (1003)	9	3 1/4" (83)
HW-2G	120 (55)	22 1/8" (562)	29 3/8" (746)	70 5/8" (1794)	18	3 1/4" (83)
CR18	135 (62)	26" (660)	34" (864)	75" (1905)	6 (open) 12 (enclosed)	3 1/4" (83)
HCR18	135 (62)	26" (660)	34" (864)	75" (1905)	18 (enclosed)	3 1/4" (83)

Adjustable Top Vent



CR18



HCR18



HW-2G



HW-2-1/2G

NU-VU® Knock Down Racks SB Series

SB-1 / SB-2

- Easy assembly
- Ships flat
- Angle slides for 13" x 18" and 18" x 26" sheet pans

Construction

- Aluminum construction
- Heavy duty casters
- One year parts warranty
- UPS shipping available



Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions			Pan Capacity (18" x 26")	Shelf Spacing in (mm)
		W in (mm)	D in (mm)	H in (mm)		
SB-1	27 (13)	21 1/2 (541)	27 1/2 (699)	31 5/8 (803)	7	3 1/4 (83)
SB-2	44 (20)	22 1/2 (572)	27 1/2 (699)	63 3/4 (1619)	17	3 1/4 (83)

Ships Knocked Down



SB-1



SB-2

NU-VU® is known for the finest baking equipment. Our design, layout and service are the cornerstones of our company. Our mission is to satisfy and surpass our customers' expectations and develop bakery and foodservice equipment that are in keeping with our reputation for quality and service.



TERMS OF SALE

NU-VU is committed to continuous improvement of the Customer experience. With that in mind, the following Terms & Conditions are for clarification to ensure smooth business transactions. If you need to return items, refer to the below for specific guidelines.

Terms and Method of Payment

All orders are subject to approval and acceptance by SELLER. No order accepted by SELLER shall be subject to cancellation, termination, suspension, change, reduction, cutback or other modification except with SELLER'S prior written consent based upon the Returns and Cancellations Policy.

SELLER'S standard terms of payment are for net 30 days from invoice date, with approved credit. The terms of credit, if extended, may be changed or credit may be withdrawn by SELLER at any time. Cash in advance (CIA) may be required on payments that are late more than twice during the calendar year or for new unestablished customers. No orders will be shipped on a Cash on Demand (COD) basis.

Late payments are subject to penalty based on the invoice subtotal in the following manner:

15 days past due – 1.0%
30 days past due – 1.5%
45 days past due – 2.0%
60 or more days past due – 10.0%

Prices do not include federal, state or local taxes, duties or other levies, now or hereafter enacted, applicable to the items deliverable under the sales order or invoice (hereinafter called ITEMS), which taxes, duties or other levies will be added by SELLER to the sales price and will be paid by BUYER unless BUYER provides SELLER with a proper Exemption certificate.

Packing for commercial shipment is included in contract price. Any special packaging, crating, or shipping instructions must be noted on BUYER'S original order and acknowledged by SELLER.

Title and Delivery

ITEMS shall be delivered FOB SELLER'S facility, and title thereto shall pass to BUYER, upon SELLER'S delivery of the ITEMS to a Common carrier for shipment to BUYER.

Any pre-paid freight must be acknowledged by SELLER.

Orders qualifying for pre-paid freight, SELLER has the right to select the means of transportation.

Any accessorial charges incurred because of Customer request will be the responsibility of the requester.

Ordering Information

How to Place an Order:

- Federal ID Numbers: required for U.S. Customs purposes from all dealers (n/a in Canada)
- All orders are subject to acceptance by the local representative and our office
- All orders must have the dealer's name, address, phone number, purchase order number, purchase order dollar amount, and method of communication for all electronic invoices and order acknowledgements.
- All orders must include a requested ship date, ship to address, job name and location
- If you have requested a freight quote and wish to use the freight rate issued by the factory, you are required to place the issued freight quote number on the purchase order when sending it to the factory.

International Orders: All international orders must specify either CE or Non-CE specific products. All purchase orders submitted to the factory must include a complete electrical questionnaire. Any orders outside the US and Canada will be subject to a 5% Warranty Administration Fee, added to the invoice. These orders may be subject to other charges, including but not limited to, utility configuration and/or CE approval fees, international documentation fees, etc. Please contact the factory for specific details. Notes: Doyon reserves the right, without prior notice, to make changes and revisions in product specifications, design and materials which, in the opinion of the company will provide greater efficiency, performance and durability.

Inspection and Acceptance

Thoroughly inspect all shipments. Do not accept a damaged or short shipment until exception is noted on the freight bill and pictures have been taken. BUYER will be held responsible for all shipments with freight bills signed free and clear.

If concealed damage is discovered, contact the freight company immediately for inspection and file a claim. Concealed damage must be reported to the carrier within 7 days of receipt. All damaged goods and shortages that are not properly documented and reported upon receipt become the sole responsibility of the BUYER.

Returns and Cancellations Policy

No returns will be accepted without an authorization number from Doyon Customer Service, utilizing the following criteria:

Order Changes & Cancellations 14 days prior to shipping may incur a 15% fee Return requests must be submitted within 30 days of Shipment Date and will incur a 50% Restocking Fee, Customer pays freight and is responsible for any damage enroute. Subject to approval for new unused equipment only.

No returns for SRO Series and KDP Series products at any time.

No returns for Custom/Special Order products at any time.

Warranty Issue

Please contact service@nu-vu.com for all NU-VU related warranty issues.

General

All prices are subject to change without notice. Orders from Authorized accounts will be accepted with the understanding that prices are those in effect at time of shipment. These prices are exclusive of all sales taxes with may be levied by State, Federal, or City governments

SELLER'S "Terms and Conditions" as set forth above shall govern all transactions.

SELLER reserves the right to change or discontinue the color, design, component content or price of any ITEMS in SELLER'S catalog or published price lists without prior notice at any time.

Terminology



JET AIR

The air moves in one direction, stops then moves the other way resulting in a bidirectional and gentle velocity air flow for exceptional baking results. This system will help you bake faster and more evenly without having to turn pans during baking time. The Jet Air fan system will save energy and labor costs.



V-AIR BY NU-VU®

NU-VU® Versatile Air Ovens employ a system that distributes controlled, heated air evenly to all areas of the oven - side to side, top to bottom, front to back. Since each product on every shelf is evenly baked, even with a full load, there is no waste of product or energy and all pans of similar products can be removed and inserted at the same time.



INTERNAL STEAM BY NU-VU®

This is a means of adding steam to the baking process without the use of an external boiler. It utilizes an adjustable spray which becomes a mist when it is heated by either elements and/or hot metal surfaces in an electric unit.



AUTOMIST BY NU-VU®

This is an automatic humidity system used in proofers. It utilizes timed bursts of water that are converted to a mist and evenly distributed throughout the unit by a moving air flow. The amount introduced is determined by adjusting the moisture control.

WARMER IN PROOFER

The proofer is not just a proofer, it can also be used as a warmer/holding cabinet to hold product at a desired temperature with or without moisture.

MOISTURE EVACUATION SYSTEM

Our patented technology draws fresh air into the oven cavity via a blower. This fresh air forces the moisture laden air that is present inside the oven out the oven vent. The oven can heat and circulate the fresh air more efficiently than moisture laden air. This makes the cooking cycle more efficient and shortens the baking time.

Terminology

FILTRATION

NU-VU® units which utilize a water line should employ a filter. Recommended for both hard & soft water and water with sediment.

FAN DELAY

A temporary suspension of the fan system, resulting in limited air flow for a small period of time at the beginning of the baking cycle that can be set anywhere from 0-5 minutes to develop the product before engaging the fan.

SHOT STEAM

The intense injection of water at the beginning of the bake cycle.

PULSE STEAM

The continuous injection of water throughout the bake cycle.

MANUAL FILL

The addition of moisture throughout the proofing cycle by implementing a water pan. This is done through the act of boiling, as the water pan rests above an element.

PROTEIN CONTENT (FOR FLOUR)

The amount of protein contained in your flour. Varies based on the type of flour.

HYDRATION PERCENTAGE

The mathematical formula calculating the absorption of water into the flour.

% AR = Water weight (lbs) divided by flour weight (lbs)

1 CANADIAN gallon of water = 10 lbs (4.54kg)

1 US gallon of water = 8.33lb (3.77kg)

Index

Note: All weights are crates weights; not actual weight of unit

Model	Lbs.	Frt Class	Page	Model	Lbs.	Frt Class	Page	Model	Lbs.	Frt Class	Page
CR18	120	250	15	PROW-8	245	100	13	RM-5T	425	92.5	6
HCR18	120	250	15	PROW-18	525	100	13	SB-1	27	UPS	16
HW-2-1/2G	75	250	15	QB-3/9	555	92.5	11	SB-2	44	UPS	16
HW-2G	120	250	15	QBT-3/9	555	92.5	11	SMOKE6	445	77.5	14
NC03	165	92.5	7	QB-4/8	630	92.5	12	SMOKE13	740	77.5	14
NC05	205	92.5	7	QBT-4/8	630	92.5	12	XO-1	165	92.5	8
NC0T5	205	92.5	7	QB-5/10	750	92.5	12	XO-1M	205	92.5	8
PRO-8	245	100	13	QBT-5/10	750	92.5	12				
PRO-16	375	100	13								



WARRANTY

Two year parts and one year labor NU-VU® limited warranty *(United States of America and Canada only)*

This NU-VU® warranty applies to all equipment that has been unaltered, properly installed and maintained in accordance with the Doyon/NU-VU® installation manuals.

NU-VU® products are warranted to the original purchaser to be free from defects in material and workmanship for a period of two years from the date of original installation, not to exceed 30 months from the product manufactured date. This warranty does not apply to equipment damaged, abused or altered accidentally or intentionally or modified by unqualified service personnel or with missing or altered serial nameplates. In order to be warranted, the equipment from the original buyer must have been purchased through a reseller from the same country.

NU-VU® agrees to repair or replace defective parts due to flaws in material or workmanship during the warranty period. Labor to repair or replace defective parts shall be warranted when performed by an authorized NU-VU® service agency. Travel over 50 miles, holiday or overtime labor charges are not covered.

Proper installation, initial inspection, or normal maintenance such as lubrication, adjustment or calibration is the responsibility of the dealer, owner-user or installing contractor and is not covered by this warranty.

This warranty does not cover wear & tear items (lights bulbs, gaskets), temperature calibration or defects resulting from handling, abuse, misuse, nor shall it extend to any unit from which the serial number has been removed or altered or the unit is modified in any way, shape, or form by an unauthorized service personnel. As well our warranty does not covered damaged by flood, fire, or other acts of god. Nor will this warranty apply as regards to the immersion element damage by hard water.

NU-VU® does hereby exclude and shall not be liable to purchaser for any consequential or incidental damages including but not limited to: damages of property, damages for loss of use, loss of time, loss of profits or income that are in direct result of a breach or warranty.

NOTE: Warranty excludes racks and bread cabinets. These items carry a (1) year limited parts warranty.

In no case, shall this warranty apply outside Canada and the Continental United States, unless the purchaser has a written agreement from NU-VU.

5600 13th Street
Menominee, MI 49858
800.338.9886



800.338.9886 | sales@nu-vu.com | www.nu-vu.com